



Olympus ATF

Product Description:

Olympus ATF is a **General Purpose ATF** manufactured from premium quality base oils and blended with a specifically balanced additive combination to provide high oxidation stability, excellent foam resistance, corrosion and wear protection, and heat resistance. This complex fluid is also compounded with a friction-modifying additive to provide smooth lock-up of clutches without chatter.

Olympus ATF is a General-purpose fluid that meets and exceeds all the old OEM specifications like **MERCON**, **Allison** and **others**.

Typical Uses:

- * Meets the Performance requirements of **Ford MERCON**
- * Also meets the performance requirements of Chrysler, Allison C4 specifications.
- * Recommended for all European OEM requirements.
- * Recommended for **Use in all General Motors Vehicles(D3H)**, where **DEXRON VI** product is **not** recommended

Features:

- * Excellent wear protection and quiet, smooth operation.
- * Superior thermal and oxidation stability.
- * Protects against rust and corrosion.
- * Outstanding seal compatibility.
- * Dyed red to detect leaks.
- * General Purpose fluid - Reduced inventory.

Typical Inspections

GRAVITY, ° API	33.0
FLASH POINT, ° C.	204
POUR POINT, ° C.	- 48
VISCOSITY:	
cP @ - 40° C. Brookfield	16500
cSt @ 40 ° C.	35.33
cSt @ 100° C.	7.16
VISCOSITY INDEX	171
COLOR, D-1500	Red

VALUES SHOWN HERE ARE TYPICAL AND MAY VARY